



FUTUR-PRIMER T PU

ADHESION PROMOTER WITHOUT YELLOWING FOR NON-POROUS SUPPORTS

One-component, colorless, non-yellowing adhesion promoter especially indicated for non-porous supports.

PROPERTIES

One-component, easy to apply and quick to cure.
Great elasticity.
Low viscosity.
Very good adhesion even on non-porous supports.
Excellent adhesion on almost all types of surfaces.
Solution as an impregnant and sealer for non-porous concrete.
No solvents required.
Does not yellow.

PHYSICAL-CHEMICAL CHARACTERISTICS

Appearance*:	Liquid
Presentation:	Metallic containers 4 Kg containers
Color:	Colorless (transparent)
Chemical nature:	Polyurethane
Density at 20 °C*:	0.830 ± 0.050 Kg/L (20 °C, ASTM D1475)
Viscosity:	40 cP (25 °C, ASTM D2196-86)
Drying time:	10-15 minutes
Flash point:	42 °C

* Quality specifications.

MODE OF USE

Before applying the product, check that the support is clean and free of traces of oil, grease, silicone, contaminating waxes or soil materials. If repair is needed, apply appropriate repair mortars.

Adheres perfectly to wet surfaces. Puddles or stagnant water should be eliminated.

Apply with a cloth moistened with the product. Its application is used for the final cleaning of the support.

Consumption: Apply with a cloth moistened with the product. Once cured, apply waterproofing membrane within 24 hours.

Touch dry: 10-15 minutes

Membrane application: 24 hours

Maintenance and cleaning: To maintain the appearance of the floor after application, all spills must be removed immediately after they have occurred. The floor must be cleaned regularly using rotating brushes, high-pressure cleaners, vacuum cleaners, using neutral detergents and appropriate waxes.

Stable for 12 months from its manufacturing date, in its original, well-closed and undamaged container. Store in a dry and cool place at temperatures between +5°C and +25°C.



Application in closed areas must be carried out ensuring proper ventilation during application and 24 hours after. Do not exceed the maximum consumption because it may affect its adhesion and durability.

Avoid the formation of puddles of the product.

Incorrect treatment of cracks and singular points can lead to a reduction in the useful life of the pavement.

To clean materials and utensils, use FUTUR-SOLVENT PU 01 before the product hardens. Once the product has hardened it can only be removed by mechanical means.

APPLICATIONS

Very useful in all types of construction companies, quick repair contracts, masonry in general, community maintenance, repair and restoration of buildings, industrial flooring, etc.

Application as:

Primer for polyurethane systems (waterproofing and flooring) on wet, dry, porous or non-porous supports.

Non-porous supports vitrified tiles, marble, glass

Limitations:

Do not apply to waterproofing swimming pools.

Before applying to other supports other than those, we recommend doing a test first to check compatibility.

The information and recommendations we provide are based on our Research and experience and we believe they are correct. Since the application of the products by our Clients is beyond our control, we cannot assume responsibilities arising from misuse of our products.